System Name: Edwards County 911 Case # 24-M-379

Date Filed: 03/12/2024

Illinois State Police (ISP) Review of Plan Modification

Requirement	Information Included	Staff Comment
Contact and 9-1-1 System information	Yes ⊠ No □	Travis Roosevelt 50 E. Main St. Albion, IL 62806 618-445-2721 (O) 618-445-7808 (C) E911@edwardscounty.illinois.gov
Verification	Yes ⊠ No □	
Letter of Intent	Yes ⊠ No □	
Plan Narrative (if incorporating an NG9-1-1 solution, narrative must include the following:	Yes ⊠ No □	Edwards County 911 is requesting to modify its 9-1-1 system by transitioning to the statewide Next Generation 9-1-1 ESInet provided by AT&T. The Edwards County 911 PSAP is tentatively scheduled to transition to the AT&T ESInet on 06/06/2024. Edwards County 911 does not accept text to 9-1-1 at this time.
Name of certified 9-1-1 system provider	Yes ⊠ No □ N/A □	AT&T
Explanation of the national standards, protocols and/or operating measures that will be followed	Yes ⊠ No □ N/A □	The 9-1-1 System will comply with all State and Federal requirements and is compliant with the National Emergency Number Association (NENA) Standards including the NENA i3 Standard for Next Generation – NENA-STA-010.3a-2021.
Explanation of measures taken to create a robust, reliable and diverse/redundant network and whether other 9-1-1 Authorities will be sharing the equipment	Yes ⊠ No □ N/A □	AT&T's ESInet solution is a combination of their IP network and Next Gen Core Services (NGCS) components that includes industry leading SLAs, management services and tools to help ensure that they provide the best possible service. The design is based on building redundant systems to avoid any single point of failure in the ESInet and the overall NG9-1-1 Network Architecture. The NG9-1-1 system will provide flexibility in the routing of calls. The ESInet being deployed has all PSAPs connected and can route calls based on not only

System Name: Edwards County 911 Case # 24-M-379

Date Filed: 03/12/2024

			location, but also by availability. In a Next Generation solution, a call
			will be answered through intelligent routing. Additionally, there will be
			more available positions to answer calls because all connected and
			tested PSAPs will be technically able to answer the call and will be
			able to dispatch or transfer the call to another PSAP. AT&T's ESInet
			provides six geographically diverse and fully redundant facilities to
			increase resiliency and survivability in natural and man-made disaster
			scenarios, with scalable capacity capable of supporting more than
			twice the 9-1-1 busy hour call for the entire United States. AT&T has documented business continuity and restoration plans, including
			complex disaster and evacuation contingencies. The 24x7 operations
			center employs an Incident Handling process modeled on FEMA's
			Incident Command System, with notifications built into the process.
			The AT&T ESInet solution will interconnect to legacy selective routers
		Yes ⊠ No □ N/A □	as defined per NENA standards. AT&T provides redundant, public
			safety grade points of presence in each LATA for OSP ingress
			locations for Legacy Network Gateways.
			AT&T will interconnect to Legacy Selective Routers to transfer and/or
			receive calls with Automatic Number Identification and Automatic
			Location Identification information to the State's NGCS via legacy
	Explanation of how the existing 9-		means through the Legacy Selective Router Gateway.
	1-1 traditional legacy wireline,		Interconnections will also allow legacy PSAPs served by legacy
	wireless and VoIP network, along		selective routers to serve as the abandonment route for PSAPs served
	with the databases, will interface and/or be transitioned into the		by the AT&T ESInet solution.
	NG9-1-1 system		Connectivity extends beyond the internal ESInet transport to external
	1100 T Toyotom		network and Originating Service Provider (OSP) interfaces. The
			ESInet supports both TDM and IP OSP ingress at geographically
			distributed Points of Interconnection (POI's). The ESInet supports
			standards-based protocol interfaces to external ESInets for call hand-
			off and call transfers. With pre-established connectivity capabilities,
			PSAPs on the ESInet have the ability to transfer calls to PSAPs on other ESInets or PSAPs that have not yet transitioned off legacy
			selective routers.
	Fundamental and become 194		Interconnection agreements will include the roles and responsibilities
	Explanation of how split	Yes ⊠ No □ N/A □	of the Parties related to the exchange of 9-1-1 traffic including but not
	exchanges will be handled		limited to, split rate centers, tandem to tandem and IP connections.

System Name: Edwards County 911 Case # 24-M-379

Date Filed: 03/12/2024

Explanation of how t will be maintained ar address errors will b and updated on a co basis	nd how e corrected	Yes ⊠ No □ N/A □	AT&T will coordinate getting the OSP's records into the AT&T ESInet database. Validation errors are corrected by the 9-1-1 Authority within their own GIS database. Updates are submitted and processed on an on-going basis.
Explanation of who was responsible for update maintaining the data minimum on a daily through Friday	ting and , at a	Yes ⊠ No □ N/A □	GIS data is submitted to the AT&T ESInet via a web-based spatial interface portal. The portal provides secure GIS file transfer. 9-1-1 Authorities can maintain their local database schema and configure database changes using attribute field mapping tools. The Spatial Interface validation engine logs errors and refers errors back to the originating 9-1-1 Authority in comprehensive reports that are retrieved in the 9-1-1 Enterprise Geospatial Database Management System.
placed on the IP 9-1 and equipment to sa from malicious attacks or	malicious attacks or threats to the system operation and what level	Yes ⊠ No □ N/A □	AT&T's ESInet cyber security policies, standards, and guidelines are consistent with industry best practices as defined by International Organization for Standardization and Control Objectives for Information and related Technology. The AT&T ESInet is a highly secure, privately managed IP network providing IP based call routing services for next generation 9-1-1 call delivery. All inbound and outbound traffic interactions are with pre-authorized entities, utilize agreed upon protocols and traverse controlled access points. Call processing and real-time data delivery are protected through both physical and logical controls. Sensitive data resides in trusted data centers that employ logical and physical access controls. All hardware and software elements deployed in a production environment go through stringent release
the system in order to ke unauthorized individ accessing it	еер		management processes that incorporate thorough penetration scan testing. Corporate and development environments are separate from production and are not used in development or system test environments. Inter-zone traffic is restricted to only that of authorized personnel and the necessary protocols destinations used to support the management and applications of the ESInet with all other traffic implicitly denied by way of redundant and diverse Session Border Controllers and stateful firewalls. All buildings and Data Center access are monitored by 24x7 security
			and access control systems.

System Name: Edwards County 911 Case # 24-M-379

Date Filed: 03/12/2024

Fi	nancial Information		
	Annual recurring 9-1-1 network costs prior to modification	Yes □ No ⊠	N/A
	Projected annual recurring 9-1-1 network costs after modification	Yes □ No ⊠	TBD
	Installation cost of the project	Yes □ No ⊠	TBD
	Anticipated annual revenues	Yes □ No ⊠	N/A
Fi	ve Year Strategic Plan	Yes □ No ⊠	
ŭ	ommunities Served	Yes ⊠ No □	
Pá	articipating Agencies	Yes ⊠ No □	
A	djacent Agencies	Yes ⊠ No □	
Ca	arrier Listing	Yes ⊠ No □	
Αt	ttachments	If changes necessitate new versions	
	Ordinances	Yes □ No ⊠	
	Intergovernmental agreement(s)	Yes □ No ⊠	
	Contracts	Yes □ No ⊠	

System Name: Edwards County 911

Case # 24-M-379

Date Filed: 03/12/2024

Back-up PSAP agreement	Yes □ No ⊠	There is no change to the current backup arrangement. Wayne County 911 (Fairfield PD) will remain the backup. Admin. Line 618-445-2721 serves as an alternate line.
Network Diagram	Yes ⊠ No □	
Call-Handling and Aid outside jurisdictional boundaries agreements	Yes □ No ⊠	
Test Plan	Yes ⊠ No □	AT&T will jointly plan the interconnecting network with the OSP. Circuits will be ordered and implemented between the OSP and the ESInet POI. AT&T will cooperatively test and turn up all trunking arrangements with the OSP. Traffic migrations from the legacy to new AT&T infrastructure will follow.

Conclusions:

Edwards County 911 is requesting a networking change to transition to the statewide AT&T Next Generation 9-1-1 network to provide Next Generation 9-1-1 service. The Edwards County 911 PSAP is tentatively scheduled to transition to the AT&T ESInet on 06/06/2024. The ISP has completed its review of the modified plan and has determined that it meets the requirements for a modified plan filing under 83 III. Admin. Code Part 1325.205.

Reviewed by: Catherine Dailey

Date: 03/19/2024